

1. First, remove boom mic connector. Use a flat blade screw driver to gently pry the connectors off the ear piece shell.
2. Turn the connector 90 degrees and slide it off the stock head band. Install boom mic connector onto the correct side of the ARC rail adapter, in reverse order. Try not to damage the rubber boot during installation.
3. Install all 4 of the connectors and get ready to connect the ARC rail adapters to the ear muffs. Install both adapters to correct side (see picture). Gently press each connector onto ear muff shell.
4. Installed adapters should look similar to the picture.



ARC RAIL / EXFIL RAIL ADAPTER INSTALL

ARC RAIL HELMET INSTALLATION



- 1 Slide the ARC rail adapter into the dovetail groove on the ARC rail, from front to back.

- 2 Position and adjust to your preference and comfort setting using the rail tab detents. Rotate and slide the ARC rail adapter to get the ear muffs to sit comfortably on your head. Make sure the helmet is securely fitted.

- 3 Run wire connecting the two ear muffs around the back and bottom of the helmet to your preference.

- 4 Make sure the helmet is securely fitted to your head before adjusting ear muff fit.

EXFIL / M-Lok HELMET INSTALLATION



1. Insert screws into adapter with the locking nuts towards the back .
2. Insert the adapter tab into the rail opening and slide in to a comfortable position. Lock in position by hand turning the screws.
3. Run wire connecting the two ear muffs around the back and bottom of the helmet to your preference.
4. Adjust boom mic length and position to your preferred location.

Please contact Code Red Headsets if you have any issues. Email us at shipping@coderedheadsets.com You may also call our toll free line (855) 486-9859.



ARC RAIL ADAPTER INSTALLATION MANUAL

